

GREATER MANCHESTER WASTE REGULATION AUTHORITY

Control of Pollution Act 1974



OUTGOING



PERMIT

Modification Notice No. M3 relating to Licence No. RD/LIC/255/82

Name and Address of Licence Holder

Irwell Street Metal Co Ltd., Kenyon Street Works, Ramsbottom, Bury.

Name and Address of Local Representative (if any)

N/A

The GREATER MANCHESTER WASTE REGULATION AUTHORITY hereby gives you notice pursuant to Section 7 of the Control of Pollution Act 1974, of modifications made to the licence granted to

Irwell Street Metal Co Ltd

under Section 5 of the Act bearing reference No. RD/LIC/255/82 as the occupier of the premises as set out in the first schedule.

The modification will delete all previous conditions and replace them with conditions in accordance with Profile Licence PFTS2/REV1.

From 18th March 1992 Licence No. RD/LIC/255/82 is to be read as incorporating modification No. M3 as set out in the second schedule.

Date of Modification Notice - 16th March 1992

Signed

D. Shipp

Solicitor to the
Waste Regulation Authority

PO Box 33,
Civic Centre,
West Street,
Oldham,
OL1 1UL.

FIRST SCHEDULE

Description of Premises

Address:

Kenyon Street Works, Ramsbottom, Bury.

Type of Waste Handling Facility:

Transfer Station - Special Wastes

Doc. Ref: 30,25 10(g)
SM

MODIFICATION M3 TO BE ATTACHED TO LICENCE NO RD/LIC/255/82 FOR IRWELL STREET
METAL CO LTD, TRANSFER STATION - SPECIAL WASTES, KENYON STREET WORKS,
RAMSBOTTOM

THE MODIFICATION DELETES ALL PREVIOUS CONDITIONS (1-16) AND PREVIOUS
MODIFICATIONS (1-2) AND REPLACES THEM WITH CONDITIONS A1 TO J6 BELOW AND
ATTACHED PLAN AND ANNEXES A - G

T A B L E O F C O N T E N T S

	<u>PAGE NO</u>
A GENERAL - SITE LICENCE, WORKING PLAN AND OPERATIONS	4
A1 Site Covered by Licence	4
A2 Operation of the Site	4
A3 Waste Disposal Operations on the Site	4
(a) Permitted Waste Disposal Operations	
(b) Prohibited Waste Disposal Operations	
A4 Permitted Waste Disposal Site Operators	4
A5 Display of Site Licence and Working Plan	5
(a) Display of Site Licence	
(b) Knowledge of Site Licence and Working Plan	
(c) Inspection of Working Plan	
A6 Working Plan	5
A7 Modification to the Working Plan	6
A8 Approval of Working Plan	6
A9 Contact Details	6
A10 Emergency Contact Details	7
A11 Notifications Under Licence Conditions	7
B PERMITTED AND NON-PERMITTED WASTES	8
B1 Permitted Types and Quantities of Waste	8
(a) Permitted Types	
(b) Maximum Total Daily Input	
(c) Maximum Quantity of Stored Waste	
(d) Maximum Quantity of Reclaimed Material	
B2 Specific Exclusions of General Waste Types	8
(a) Waste in Sludge or Liquid Form	
(b) Waste in Drums	
(c) Explosive Wastes	
(d) Violently Reactive Wastes	
(e) Pressurised Wastes	
B3 Pre-Treated Wastes	9
B4 Special Wastes	9
B5 Malodourous Wastes	9
B6 Incompatible Wastes	9
C CONTROL OF WASTE DISPOSAL OPERATIONS	10
C1 Checks on Incoming Wastes	10
(a) Visual Checks Prior to Deposit	
(b) Analyses Prior to Deposit	
(c) Visual Checks Following Deposit	
(d) Additional Checks on Incoming Special Waste	
C2 Non-Conforming Wastes	11
C3 Sampling	11
C4 Special Wastes	12
C5 Asbestos	12
C6 Waste in Drums	12

D	SITE RECORDS	13
D1	Site Records	13
	(a) Inputs/Deliveries of Waste to the Site	
	(b) Outputs/Removals of Waste from the Site	
	(c) Special Wastes	
	(d) Analysis of Wastes	
	(e) Monitoring of Surface Waters	
	(f) Monitoring of Groundwater	
	(g) Monitoring of Water Within the Bunds	
D2	Retention and Surrender of Records	14
D3	Submission of Copies of Records to the Waste Regulation Authority	15
	(a) Inputs/Deliveries of Waste to the Site	
	(b) Outputs/Removals of Waste from the Site	
	(c) Special Waste Records	
	(d) Monitoring of Surface Water	
	(e) Monitoring of Groundwater	
	(e) Special Wastes	
	(g) Analysis of Waste	
D4	Inspection of Records	16
D5	Outstanding Records	16
E	SITE FACILITIES AND INFRASTRUCTURE	17
E1	Site Office	17
E2	Site Identification Board	17
E3	Site Security & Fencing	17
E4	Site Access	17
E5	Fuel Storage Tank	17
F	SITE OPERATIONS	18
F1	Opening Hours	18
F2	Staffing	18
F3	Machinery, Plant & Equipment	18
F4	Temporary Cessation of Operations	18
G	WASTE DISPOSAL OPERATIONS ON THE SITE	19
G1	Site Preparation and Engineering Works	19
G2	Input or Delivery of Wastes	19
G3	Sorting and Segregation of Wastes	19
G4	Storage of Solid Wastes	19
G5	Output or Removal of Wastes	20
G6	Reclaimed Materials	20
G7	Special Waste Disposal Operations on the Site	20
G8	Liquid Wastes	20
H	ENVIRONMENTAL CONTROLS	21
H1	Fires	21
H2	Loose Waste	21
H3	Control of Windblown Waste	21
H4	Control of Weeds	21
H5	Vermin & Insects	21
H6	Amenities	21
H7	Suppression of Dust	21
H8	Cleanliness of Vehicles	21
H9	Sheeting of Loads	21
I	POLLUTION CONTROLS	22
I1	Drainage Onto or From Land	22
	(a) Surface Water Run Off	
	(b) Discharge of Surface Water	
I2	Discharge to Drains, Sewers or Watercourses	22

I3	Removal of Contaminated Water	22
	(a) Water from Site Surface	
	(b) Water from Storage Area Bunds	
I4	Monitoring of Surface Water Arisings	23
	(a) Surface Water Monitoring Programme	
	(b) Initial Measurements	
	(c) Recording of Surface Water Monitoring Results	
	(d) Retention of Records	
	(e) Submission of Copies of Monitoring Records to the Waste Regulation Authority	
	(f) Revisions to the Surface Water Monitoring Programme	
	(g) Trigger Levels	
I5	Monitoring of Groundwater	24
	(a) Groundwater Monitoring Programme	
	(b) Initial Measurements	
	(c) Recording of Groundwater Monitoring Results	
	(d) Retention of Records	
	(e) Submission of Records to the Waste Regulation Authority	
	(f) Revisions to the Groundwater Monitoring Programme	
	(g) Trigger Levels	
I6	Control of Aerial Emissions from the Site	26
J	SITE PREPARATION AND MAINTENANCE	27
J1	Preparation and Maintenance of Site Surface	27
J2	Surface Water Drainage and Monitoring System	27
J3	Groundwater Monitoring System	27
J4	Construction of Bays	27
J5	Construction of Bunds	27
J6	Maintenance of Site	28
ANNEXES		
A	PERMITTED WASTE TYPES	29
B	SOIL CLASSES A TO E - LIMITS OF RANGES FOR CONTAMINATION LEVELS	45
C	ANALYSIS OF SAMPLES OF WASTE	47
D	ANALYSIS OF SAMPLES OF (a) SURFACE WATER, (b) GROUNDWATER	49
E	SCHEDULE OF SITE RECORDS	50
F	CODE OF PRACTICE FOR THE DISPOSAL OF DRUMMED WASTE TO LANDFILL	53
G	TESTING OF LIQUIDS IN BUNDS	56

A GENERAL

A1 Site Covered By Licence

These licence conditions shall apply to the site shown hatched black on the attached plan RD/LIC/255/82/M3/P1.

A2 Operation of the Site

The site shall be operated in accordance with the following licence conditions and in accordance with the methods of operation described in the current issue of the Working Plan. The current issue of the Working Plan shall be in accordance with the requirements of Condition A6 below. The Working Plan shall not be altered or modified other than in accordance with Condition A7 below. In the event of any proposals or details of operations contained in the Working Plan being in conflict with these licence conditions, the licence conditions shall prevail.

A3 Waste Disposal Operations on the Site

(a) Permitted Waste Disposal Operations:

Permitted waste disposal operations on the site shall consist only of the following operations:

- (i) input or delivery of wastes to the site, carried out in accordance with the requirements of Conditions C1 to C7, D1, G2 and the other relevant conditions of this licence;
- (ii) sorting and segregation of wastes on the site, carried out in accordance with Conditions C1, G3 and the other relevant conditions of this licence;
- (iii) storage of wastes on the site, carried out in accordance with Conditions C3, G4 and other relevant conditions of this licence;
- (iv) output or removal of wastes from the site, carried out in accordance with the requirements of Conditions C4, D1 and the other relevant conditions of this licence;
- (v) baling of wastes as described in the Working Plan.

(b) Prohibited Waste Disposal Operations:

Notwithstanding the provisions of Condition A3(a) above, the following waste disposal operations shall not take place on the site:

- (i) landfill operations;
- (ii) processing of wastes other than sorting, baling, segregation and storage;
- (iii) incineration or distillation.

A4 Permitted Waste Disposal Site Operators

The permitted waste disposal operations specified in Condition A3(a) shall only be carried out by the licence holder or persons in his direct employment and managerial control, except for:

- (i) site preparation and engineering works, which may be carried out by contractors as specified in the Working Plan;

- (ii) carriage of wastes to the point of initial deposit on the site;
- (iii) carriage of wastes from the point of despatch from the site.

A5 Display of Site Licence and Working Plan

(a) Display of Site Licence:

A copy of this site licence including the conditions and any modification thereto shall be displayed at all times in the site control office in a prominent position.

(b) Knowledge of Site Licence and Working Plan:

The contents of the site licence and its conditions together with the contents of the current issue of the Working Plan shall be made known to:

- (i) any person who is given responsibility for the management and control of the site; and

- (ii) all site operatives;

and shall be made available to:

- (iii) anyone wishing to use the site and whom the operator intends to allow to use the site.

(c) Inspection of Working Plan:

The current issue of the Working Plan shall be made available for inspection at the site office at any reasonable time by:

- (i) any person who is given responsibility for the management and control of the site;

- (ii) any site operatives;

- (iii) any authorised representative of the Waste Regulation Authority;

- (iv) the local Environmental Health Officer.

A6 Working Plan

- (a) For the purposes of this licence, the current issue of the Working Plan shall consist of the latest issue or modification of the Working Plan which has been approved in writing by the Waste Regulation Authority in accordance with Condition A7 below.

- (b) The detailed format and contents of the Working Plan shall be in accordance with the requirements of the Waste Regulation Authority.

- (c) Within one calendar month of its approval by the Waste Regulation Authority, a copy of the current issue of the Working Plan shall be submitted by the licence holder to:

- (i) the National Rivers Authority (North West Region); and
- (ii) the local Environmental Health Authority.

A7 Modifications to the Working Plan

The current issue of the Working Plan shall not be revised, altered or otherwise modified unless:

- (a) a copy of the proposed revision, alteration or other modification has been submitted to the Waste Regulation Authority in writing; and
- (b) the proposed revision, alteration or other modification has been approved in writing by the Waste Regulation Authority.

A8 Approval of Working Plan

No waste shall be received on the site unless the current issue of the Working Plan has been submitted to and approved in writing by the Waste Regulation Authority, in accordance with Condition A6.

In the event of a modification to the current issue of the Working Plan being requested in writing by the licence holder or required in writing by the Waste Regulation Authority, a timescale for the submission and approval of the modification shall be agreed in writing with the Waste Regulation Authority within two weeks of the written request or written requirement being made. No waste shall be received on the site other than in accordance with the approved Working Plan beyond the agreed timescale for submission and approval unless either:

- (i) the modification has been submitted to and approved in writing by the Waste Regulation Authority in accordance with Condition A7; or
- (ii) an extension to the timescale has been agreed in writing with the Waste Regulation Authority; or
- (iii) the requirement for a modification has been withdrawn in writing by the Waste Regulation Authority.

A9 Contact Details

No waste shall be received until the licence holder has provided to the Waste Regulation Authority in writing the name, business address and telephone number of:

- (a) the person or persons having authority to accept or reject waste at the site;
- (b) the person or persons responsible for the day-to-day control of operations on the site;
- (c) the person or persons responsible for site security; and
- (d) the person or persons responsible for ensuring that the conditions of this licence are complied with.

Any change in these details shall be notified in writing to the Waste Regulation Authority forthwith.

A10 Emergency Contact Details

No waste shall be received until the licence holder has provided to the Waste Regulation Authority in writing the name, address and telephone number of a responsible person for contact in the event of an emergency arising in connection with the facility:

- (a) during normal operating hours; and
- (b) outside normal operating hours.

Any change in these details shall be notified in writing to the Waste Regulation Authority forthwith.

A copy of the above information shall be submitted by the licence holder in writing to the local Environmental Health Authority.

A11 Notifications Under Licence Conditions

Any notification which the licence holder is required to make under these conditions shall be made to:-

The Chief Officer
Greater Manchester Waste Regulation Authority
6th Floor
Blackfriars House
Parsonage
Manchester
M3 2JA

Telephone Number 061-832-2776

B **PERMITTED WASTES**

B1 **Permitted Types and Quantities of Waste**

(a) Permitted Types:

Only those types of waste specified in Annex A to this licence shall be received at the site. If a particular waste type is not listed in Annex A as a permitted waste type, then it shall not be received at the site.

(b) Maximum Daily Input:

(i) Total Permitted Wastes:

The maximum total daily input of wastes to the site shall be 350 tonnes/day.

(ii) Waste Groups:

Within the constraints of Conditions B1(a) and (b)(i) above the maximum total daily input of each Waste Group to the site shall be as specified in Annex A, as follows:

Group 1:	280 tonnes/day
Group 2:	280 tonnes/day
Group 3:	280 tonnes/day
Group 4:	250 tonnes/day
Group 5:	60 tonnes/day

(iii) Waste Types:

Within the constraints of Conditions B1(a), b(i) and b(ii) above, the maximum input of each permitted waste type to the site shall be as specified against that waste type in Annex A to this licence.

(c) Maximum Quantity of Stored Wastes:

The maximum quantity of solid waste stored on the site at any time shall not exceed the storage volume of the bays specified in Condition G4. The maximum quantity of waste in liquid or sludge form stored on the site shall not exceed the storage volume of the bunds as specified in Condition G5.

(d) Maximum Quantity of Reclaimed Materials:

The maximum quantity of reclaimed materials stored on the site at any time shall not exceed the storage volume of the skips and other containers specified in Condition G6.

B2 **Specific Exclusions of General Waste Types**

Notwithstanding the provisions of Condition B1 above, the following general exclusions of waste types shall apply to the site:

(a) Waste in Sludge or Liquid Form:

Only special wastes in sludge or liquid form which are also permitted wastes under Condition B1 shall be received at or deposited upon the site.

(b) Explosive Wastes:

No wastes shall be deposited which are inherently explosive.

(c) Violently Reactive Wastes:

No wastes shall be deposited which react violently with water.

(d) Pressurised Wastes:

No wastes shall be deposited which:

- (i) are contained in pressurised containers; or
- (ii) consist of pressurised containers, except for aerosol cans which constitute an inherent component of household refuse, where this waste type is permitted to be deposited.

B3 Pre-Treated Wastes

Where waste types are not permitted to be deposited under the provisions of this licence, then those wastes shall not be deposited whether or not they have been packaged, placed in other containers or waste materials, or pre-treated by any form of solidification or encapsulation.

B4 Special Wastes

Special wastes, as defined by the "Control of Pollution (Special Waste) Regulations 1980" (or any subsequent replacement legislation), shall only be received, sorted, segregated, stored and removed in accordance with Conditions C1 and G7.

B5 Malodourous Wastes

Wastes that could give rise to an objectionable odour to persons outside the site boundary shall be handled on the site in such a manner as to prevent such nuisance arising, in accordance with the preventive measures specified in the Working Plan. Such measures to be included in the Working Plan shall be following consultation with the Environmental Health Authority for the area of the site.

Aerial emissions from the site shall be controlled in accordance with Condition I6.

B6 Incompatible Wastes

Wastes of different types which are liable to react with each other so as to cause either:

- (i) fire;
 - (ii) explosion; or
 - (iii) the formation of obnoxious or toxic fumes, vapours or gases,
- shall be kept separate and stored in clearly marked, segregated areas and/or containers.

C CONTROL OF WASTE DISPOSAL OPERATIONS

C1 Checks on Incoming Waste

All loads of waste received at the site shall be checked prior to deposit to ensure that the waste types conform to the requirements of Conditions B1 and B2 of this licence. The checks shall consist of the following:

(a) Visual Checks Prior to Deposit:

A visual check shall be made of the contents of all incoming loads to ensure their suitability for deposit at the site. Any cover sheets or nets shall be removed from the load for this check to be carried out.

(b) Analyses Prior to Deposit:

- (i) All soils for which there is reason to suspect that the soil may be contaminated above the levels permitted for Soil Class A (as defined in Annex B to this licence) shall be sampled and the samples subjected to a Soil Analysis as specified in Annex C to this licence prior to deposit on the site.
- (ii) All wastes for which there is reason to suspect that the waste may be contaminated above the levels permitted for that waste type (as specified in Annex A and as defined in Annex B to this licence), shall be sampled and the samples subjected to a Full Analysis as specified in Annex C to this licence prior to deposit on the site.
- (iii) All special wastes and all wastes specified in Annex A to this licence as requiring analysis, shall be sampled and the samples subjected to a Full Analysis as specified in Annex C to this licence prior to deposit on the site unless such wastes have been previously analysed and the results of the analysis have been obtained in writing by the licence holder.
- (iv) All such Soil Analyses, Basic Analyses and Full Analyses shall be in accordance with the list of parameters and methods of analysis specified in Annex C to this licence. The basis of the sampling for such analyses (every load or random samples from a specified proportion of the loads) shall be in accordance with the basis specified in Annex E to this licence.
- (v) Results of all such analyses carried out in accordance with (i) or (ii) or (iii) above shall be recorded in writing and retained in accordance with Condition D1.

(c) Visual Checks Following Deposit:

All wastes deposited at the site shall be checked immediately following deposit and during sorting, segregation and storage, to ensure their continued suitability for disposal operations at the site and for final disposal at the destination site.

(d) Additional Checks on Incoming Special Waste:

In addition to the checks carried out under C1(a), (b) and (c), each load of special waste entering the site shall be checked against the description of the load as declared on the 'Consignment Note for the Carriage and Disposal of Hazardous Wastes' accompanying the load. Any special waste not conforming to the declared description shall be placed in the special waste bay. The action to be taken regarding such waste must be agreed with the Waste Regulation Authority.

C2 Non-Conforming Wastes

All waste not conforming to the requirements of Conditions B1 and B2 shall be turned away or removed from the site in accordance with the following:

- (a) Where such non-conforming waste is not detected prior to deposit by the checks specified in Condition C1(a), C1(b) and C1(d), but is detected following deposit by the checks specified in Condition C1(c), it shall be re-loaded immediately onto the vehicle making the deposit. Each such incident shall be recorded in the site records specified in Condition D1(a) and D1(b).
- (b) Where such non-conforming waste is not detected prior to deposit by the checks specified in Condition C1(a), C1(b) and C1(d), but is detected following deposit by the checks specified in Condition C1(c), but due to circumstances outside the operator's control it is impracticable to re-load the waste onto the vehicle making the deposit, it shall be stored in a container in a specified area previously agreed in writing with the Waste Regulation Authority and incorporated in the Working Plan. The waste shall be removed to a suitably licensed site by the end of a period of 5 working days. Each such incident shall be recorded in the site records specified in Condition D1(a) and D1(b).
- (c) Any special waste not conforming to the declared description shall be placed in the designated special waste bay and the Waste Regulation Authority notified immediately in order that the most appropriate course of action under C2(a) and (b) can be formally approved.

C3 Sampling

Samples of any waste entering the site or undergoing disposal on the site and samples of any gaseous, liquid or particulate emissions from the site may be taken by or under the direction of the Waste Regulation Authority.

The operator shall provide any reasonable assistance in the form of site personnel and/or equipment to the Waste Regulation Officers on request, to enable such samples to be obtained.

Any information required to enable sampling to be carried out in accordance with the requirements of the "Control of Substances Hazardous to Health (COSHH) Regulations 1988" (or any subsequent replacement legislation) shall be provided forthwith to the Waste Regulation Authority on request.

C4 Special Wastes

All special wastes notified to the site shall be checked according to Condition C1 and deposited into a totally enclosed and lockable container positioned in the special waste storage bay in accordance with Condition G7. Any special wastes which are not permitted under Annex A and which are delivered to the site and detected by the checks specified in Conditions C1(a), (b), (c) or (d) shall be placed within the Special Waste bay as an emergency measure pending either the return of the waste to the producer or removal to a suitably licensed waste disposal facility. The licence holder shall notify the Waste Regulation Authority immediately of all such emergencies in order to formally agree the removal procedure which shall be in accordance with the Control of Pollution (Special Waste) Regulations 1980 (or any subsequent replacement legislation).

C5 Asbestos

Asbestos and asbestos-contaminated waste as defined in Annex A to this licence shall be disposed of in accordance with the requirements of Waste Management Paper No 18 (or any subsequent replacement waste management paper by whatever name). Asbestos wastes which consist of, or are liable to give rise to asbestos fibres shall be treated as a Special Waste and shall be handled in accordance with the relevant Conditions of this licence regarding Special Wastes.

C6 Waste in Drums

Any waste received at the site in drums shall be treated and/or segregated in such a manner that their transfer to landfill does not contravene the requirements of the Code of Practice for the Disposal of Drummed Waste to Landfill (attached as Annex F to this licence), where it is a requirement of the relevant landfill site licence that this Code of Practice shall apply.

D SITE RECORDS

D1 Site Records

The operational site records shall be kept as specified in (a) to (e) inclusive below, and as summarised in Annex E to this licence. The form of the records shall be specified in the Working Plan.

(a) Inputs/Deliveries of Waste to the Site:

- (i) A record shall be kept of the types and quantities of waste delivered to the facility. The form of the record shall be agreed in writing with the Waste Regulation Authority and shall include details of the person or company delivering the waste, the time and date of the delivery, the registration number of the vehicle, the name of the driver, and a description of the waste and the quantity of waste in the load. This record shall be signed by the site operative checking the load in accordance with Conditions B1 to B4 of this licence, and by the driver of the vehicle delivering the waste.
- (ii) The recorded description of the waste shall conform with the waste deposited against that record.
- (iii) A daily summary of the above records shall be made within five working days of the original records being made. This summary shall record the following details for each day:

Waste type (as specified in Annex A)
Total quantity of waste type received (tonnes)
Number of loads of each waste type (vehicles)

(b) Outputs/Removals of Waste from the Site:

- (i) A record shall be kept of the types and quantities of waste removed from the facility. The form of the record shall be agreed in writing with the Waste Regulation Authority and shall include details of the person or company removing the waste, the time and date of the removal, the registration number of the vehicle, the name of the driver, a description of the waste and the quantity of waste in the load and details of the final destination of the waste. This record shall be signed by the site operative checking the load, and by the driver of the vehicle removing the waste.
- (ii) The recorded description of the waste shall conform with the waste removed against that record.
- (iii) A daily summary of the above records shall be made within five working days of the original records being made. This summary shall record the following details for each day:

Waste type (as specified in Annex A)
Total quantity of waste type received (tonnes)
Number of loads of each waste type (vehicles)

(c) Special Wastes:

- (i) A daily record shall be kept of all Special Wastes received and in storage on the site. This record shall be cross-referenced to the records of the waste deliveries and removals kept under Conditions D1(a) and (b). The daily record shall contain the following details:-

- (ii) Records shall be kept of all removals from the site of Special Wastes, in accordance with the "Control of Pollution (Special Waste) Regulations 1980", (or any subsequent replacement legislation) and in accordance with Condition C4.

Waste type, quantity and condition
Container type and condition
Location

(d) Analyses of Wastes:

A record shall be kept of all analyses of wastes carried out in accordance with Condition C1. This record shall include the results of all such analyses. The record of each analysis shall include a summary interpretation of the results.

(e) Monitoring of Surface Waters:

A record shall be kept of all conductivity measurements and all analyses of samples of surface waters arising from the site and in watercourses adjacent to the site in accordance with the requirements of Condition I4. The record of each such analysis shall include a summary interpretation of the results.

(f) Monitoring of Groundwater:

Except where previously agreed in writing with the Waste Regulation Authority in accordance with Condition I5, a record shall be kept of all conductivity measurements and all analyses of samples of groundwaters in the vicinity of the site in accordance with the requirements of Condition I5. The record of each such analysis shall include a summary interpretation of the results.

(g) Monitoring of Water Within the Bunds:

A record shall be kept of all analyses of waters collected within the special waste storage bunds in accordance with Annex G of this licence. A record of the discharge of all such waters to drain/sewer or the removal of such waters to a suitably licensed site shall be kept in accordance with Condition I3(b)(ii) of this licence, and submitted to the Waste Regulation Authority in accordance with Condition I3(b)(iv) of this licence.

D2 Retention and Surrender of Records

All records required to be kept under Condition D1 shall be securely kept in the format specified in the Working Plan, at the site office or at the licence holder's offices at:

Kenyon Street Works
Ramsbottom
Bury
Lancashire

The site operator shall keep these records for the duration of the site licence unless otherwise authorised in writing by the Waste Regulation Authority. The licence holder shall surrender these records to the Waste Regulation Authority on termination of this site licence, whether by surrender or revocation.

D3 Submission of Copies of Records to the Waste Regulation Authority

Copies of the records specified in Condition D1 shall be sent in writing to the Waste Regulation Authority as follows (as summarised in Annex E to this licence):

(a) Inputs/Deliveries of Waste to the Site:

A copy of the daily summaries for each calendar month shall be sent to the Waste Regulation Authority within two weeks of the end of that calendar month.

(b) Outputs/Removals of Waste from the Site:

A copy of the daily summaries for each calendar month shall be sent to the Waste Regulation Authority within two weeks of the end of that calendar month.

(c) Special Waste Records:

A copy of the daily summaries for each calendar month, as specified in Condition D1(c)(i) shall be sent to the Waste Regulation Authority within two weeks of the end of that calendar month.

(d) Monitoring of Surface Water:

(i) Conductivity Measurements:

A copy of the records of such conductivity measurements of surface waters taken in accordance with the requirements of Conditions D1(e) and I4 shall be sent to the Waste Regulation Authority in accordance with the requirements of Condition I4.

(ii) Analyses of Samples:

A copy of the records of analyses of samples of surface waters taken in accordance with the requirements of Conditions D1(e) and I4 shall be sent to the Waste Regulation Authority in accordance with the requirements of Condition I4.

(e) Monitoring of Groundwater:

(i) Conductivity Measurements:

A copy of the records of conductivity measurements of groundwater taken in accordance with the requirements of Conditions D1(f) and I5 shall be sent to the Waste Regulation Authority in accordance with the requirements of Condition I5.

(ii) Analyses of Samples:

A copy of the records of analyses of samples of groundwater taken in accordance with the requirements of Conditions D1(f) and I5 shall be sent to the Waste Regulation Authority in accordance with the requirements of Condition I5.

(f) Analysis of Wastes:

A record shall be kept of all analyses of soils and other wastes carried out in accordance with Condition C1(b). This record shall include results of all such analyses. The record of each such analysis shall include a summary interpretation of the results.

D4 Inspection of Records

All records required to be kept under Conditions D1 and D2 of this licence must be made available to any authorised representative of the Waste Regulation Authority for inspection at any reasonable time.

D5 Outstanding Records

In the event of failure to comply with the requirements of Conditions D1, D2, D3 or D4, the outstanding records shall be submitted in writing or by facsimile transmission to the Waste Regulation Authority forthwith.

E SITE FACILITIES AND INFRASTRUCTURE

E1 Site Office

No waste shall be received at the site until a site office has been provided as specified in the Working Plan. It shall be adequately equipped and manned to allow the requirements of the conditions of this licence to be routinely carried out.

E2 Site Identification Board

No waste shall be received unless a site identification board of durable material and finish is being prominently displayed at the site entrance showing the hours when the site is open and giving the name of the site, the name, address and telephone number of the operator (and his local agent) and the Waste Regulation Authority responsible for issuing the site licence.

The board shall include a prominent instruction to incoming drivers to report at the site office in order to have their loads checked prior to deposit.

E3 Site Security

No waste shall be received until the site is made secure in the manner specified in the Working Plan. All site fencing, walls, gates and doors shall be maintained to a standard sufficient to prevent unauthorised access.

Site fencing and gates shall be inspected each working day, and any damage or holes repaired within one working day (24 hours) of being detected. Gates and/or doors shall be locked out of working hours other than in an emergency situation, and in any case whenever the site is not manned.

E4 Site Access

Access to the site for incoming and outgoing waste shall only be from Kenyon Street, through the gates/doors specified in Condition E3.

E5 Fuel Storage Tank

All fuel stored on the site other than in vehicle fuel tanks shall be contained in a bunded tank provided in accordance with the Working Plan. The bund for this tank shall be impervious and shall provide containment for at least 110% of the maximum volume of the tank.

F **SITE OPERATIONS**

F1 **Opening Hours**

The site shall only be open for the receipt or removal of waste during the hours:-

Monday to Friday	0800 - 1800
Saturday	0800 - 1300
Sunday	No Receipts or Removals
Bank Holidays	No Receipts or Removals
Other Public Holidays	No Receipts or Removals

F2 **Staffing**

Appropriately trained and experienced supervisory and/or operating staff shall be made available as and when required to ensure that the conditions of this licence are fulfilled. The appropriate level of training shall be as specified in the Working Plan, and shall in particular address the need for checking, screening and testing incoming waste, and for prevention and monitoring of pollution and detriment to the local environment.

A minimum of two operatives, at least one of whom shall be an appropriately trained and experienced supervisor, shall be on site whenever waste is being received, handled or removed. Staff shall be trained in the use of fire fighting equipment provided in accordance with Condition F3.

F3 **Machinery, Plant and Equipment**

An appropriate level of machinery, plant and equipment shall be provided to ensure that all incoming waste is dealt with in accordance with the conditions of this licence. The machinery, plant and equipment shall be specified in the Working Plan, and operational instructions for the machinery, plant and equipment shall be kept in the site office. Fire fighting equipment specified in the Working Plan shall be provided and maintained in accordance with the requirements of the Local Fire Authority.

In the event of any breakdown in such machinery, or equipment which results in either waste or surface water drainage arisings not being dealt with in accordance with the conditions of this licence, the site shall be closed until such time as the defective items are repaired or replaced, unless otherwise authorised by the Waste Regulation Authority.

F4 **Temporary Cessation of Operations**

All temporary cessations of operations which require the transfer or diversion of waste delivered at the facility to facilities elsewhere shall be notified in writing forthwith to the Waste Regulation Authority.

G WASTE DISPOSAL OPERATIONS ON THE SITE

G1 Site Preparation and Engineering Works

All site preparation and engineering works specified in the Working Plan shall be carried out in accordance with the requirements of Conditions J1 to J5 inclusive.

No waste shall be deposited on the site until:

- (a) the site preparation and engineering works specified for that area in the Working Plan have been carried out in accordance with the requirements of Conditions J1 to J5, and these works have been approved in writing by the Waste Regulation Authority; and
- (b) all test results required in respect of such site preparation and engineering works have been submitted in writing to, and approved in writing by, the Waste Regulation Authority.

G2 Input or Delivery of Wastes

All waste delivered to the site shall be checked in accordance with Condition C1 to ensure that it conforms to the requirements of Conditions B1 and B2.

All waste delivered to the site shall be recorded in accordance with Condition D1(a).

All waste accepted at the site shall be deposited within the bays or bunds, as constructed in accordance with Conditions J4 and J5 and specified in the Working Plan. All Special Waste delivered to the site shall be checked and recorded in accordance with Condition G7.

G3 Sorting and Segregation of Wastes

All sorting and segregation of wastes on the site shall take place within the designated and prepared area of the site specified in the Working Plan. All Special Waste shall be sorted and segregated in accordance with Condition G7.

G4 Storage of Solid Wastes

All waste deposited on the site either before, during or after sorting and segregation shall be stored within the 4 bays specified in Condition G2, except for those reclaimed materials specified in Condition G6. All Special Wastes shall be stored within the Special Waste bay in a totally enclosed and lockable container in accordance with Condition G7.

Wastes shall not be stored above the maximum permitted height of 2 metres above ground level or beyond the front boundaries of the bays. The maximum storage volume of each bay shall be as follows:

Bay 1	100m ³	Special Waste Bay
Bay 2	170m ³	Non-Special Waste Bay
Bay 3	170m ³	Non-Special Waste Bay
Bay 4	170m ³	Non-Special Waste/Compactor Bay

The maximum permitted storage height and the front boundaries of the bays shall be shown by conspicuous lines painted on the walls and front edge of the bays in accordance with Condition J4 and as specified in the Working Plan.

No putrescible wastes shall remain on the site or in any bay or container on the site for periods in excess of 24 hours.

No other waste shall remain on the site or in any bay for periods in excess of 5 days, with the exception of the following:

reclaimed material within the skips and containers specified in Condition G6, which shall not remain on the site for periods in excess of one calendar month.

G5 Output or Removal of Wastes

All wastes removed from the site shall be recorded in accordance with Condition D1(b) and (c).

G6 Reclaimed Materials

Reclaimed plastics, paper, cardboard and metals which are separated from the wastes deposited in the bays, shall be stored within skips or other containers as specified in the Working Plan. Such skips and containers shall be kept within the area of the site specified in the Working Plan in accordance with Condition G3, until their removal from the site. All such reclaimed materials removed from the site shall be recorded in accordance with Condition D1(b).

The maximum total storage volume of such skips and containers shall be 300m³.

G7 Special Wastes

- (a) All Special Waste delivered to the site shall be checked in accordance with Condition C1.
- (b) All Special Waste delivered to the site shall be segregated and stored within the Special Waste storage bay in accordance with Conditions B6 and C4.
- (c) All Special Waste removed from the site shall be in accordance with the 'Control of Pollution (Special Waste Regulations 1980)' or any subsequent replacement legislation.
- (d) All surface water and other uncontaminated liquids within the Special Waste storage area shall be collected by means of bunding specified in Condition J5.
- (e) All surface water and other liquids collected within the Special Waste storage area bund shall be tested prior to discharge as specified in Annex G to this licence. All such tests shall be recorded in accordance with Condition D1(g).
- (f) A record shall be kept of all conductivity measurements and analysis of samples of all liquids arising within the Special Waste bunded area in accordance with the requirements of Condition I3(b). The record of such analysis shall include a summary interpretation of the results.

G8 Liquid Wastes

All liquid wastes shall be stored in impervious bunds which shall provide containment for at least 110% of the maximum volume of the largest container within the bund.

H ENVIRONMENTAL CONTROLS

H1 Fires

No waste material shall be burnt within the boundaries of the site. Any fire at the site shall be regarded as an emergency and immediate action shall be taken to extinguish it. All such outbreaks of fire shall be notified forthwith to the Waste Regulation Authority in accordance with the terms of Condition A11.

H2 Loose Waste

At least once a day any loose waste which may be lying on the site shall be gathered and disposed of in such a way as to keep the site tidy.

H3 Control of Windblown Waste

All reasonable precautions shall be taken in accordance with the Working Plan to ensure that waste which becomes windblown is retained within the curtilage of the site.

H4 Control of Weeds

The site shall be maintained in a tidy condition in accordance with the Working Plan, and where necessary action shall be taken to control or destroy weeds.

H5 Vermin & Insects

Precautions shall be taken as specified in the Working Plan to deal effectively with any vermin and insects on the site.

H6 Noise, Vibration and Aerial Emissions

Measures as specified in the Working Plan shall be undertaken so as to prevent detriment through noise and vibration to the amenities of the adjoining locality. Detriment shall be defined by the levels specified in the Working Plan, as agreed in writing with the Environmental Health Authority for the area of the site.

Aerial emissions from the site shall be controlled in accordance with Conditions B5 and I6.

H7 Suppression of Dust

Whenever necessary the site surface, incoming loads and waste awaiting deposit shall be sprayed with water to suppress the emission of dust, and in any event shall be so sprayed if requested by officers of the Waste Regulation Authority.

H8 Cleanliness of Vehicles

The licence holder shall ensure that all measures as specified in the Working Plan are carried out so as to prevent any vehicles from leaving the site or access roads between the highway and the site, in such a condition that they foul the highway with mud or other material.

H9 Sheeting of Loads

The licence holder shall take all reasonable steps as specified in the Working Plan to ensure that all loads of waste in open containers being received at the site are adequately sheeted.

All loads of waste in open containers being removed from the site shall be adequately sheeted.

I POLLUTION CONTROLS

I1 Drainage Onto or From Land

(a) Surface Water Run Off:

All surface water run off from the site shall be collected in the site surface water drainage system specified in the Working Plan, and shall be monitored in accordance with Condition I4.

(b) Discharge of Surface Water:

No such water shall be discharged to any watercourse without the written permission of the National Rivers Authority (NW Region). Where permitted, such discharges shall be monitored in accordance with Condition I4.

I2 Discharge to Drains, Sewers or Watercourses

No waste, or water contaminated with waste, shall be discharged or allowed to enter any drain, sewer or watercourse other than in accordance with a consent issued by the National Rivers Authority (NW Region) in the case of watercourses or North West Water PLC in the case of drains or sewers. All such discharges shall be monitored in accordance with Condition I4.

I3 Removal of Contaminated Water

(a) Water from Site Surface:

All contaminated surface water shall be collected by means of the surface drainage system specified in the Working Plan in accordance with Condition J2 of the licence. Unless a discharge consent for such contaminated water is in force as specified in Condition I2, such contaminated water shall be removed to a suitably licensed site at regular intervals as specified in the Working Plan. All removals of contaminated water to a suitably licensed site shall be recorded in accordance with the requirements of Condition D1(b).

(b) Water from Storage Area Bunds:

(i) Collection:

Within the storage area all surface water and other uncontained liquids shall be collected by means of the bunding specified in Condition J5.

(ii) Testing:

All surface water and other liquids collected within the bunds shall be tested prior to discharge as specified in Annex G to this licence. All such tests shall be recorded in accordance with Condition D1(d).

(iii) Removal:

Unless a discharge consent for such uncontaminated water is in force as specified in Condition I2, such contaminated water shall be removed to a suitably licensed site at regular intervals as specified in the Working Plan. All removals of contaminated water to a suitably licensed site shall be recorded in accordance with the requirements of Condition D1(b).

- (iv) Submission of Copies of Records to the Waste Regulation Authority:

A copy of the records made in accordance with the requirements of Condition D1(g) shall be submitted in writing to the Waste Regulation Authority as follows:

- (i) tests carried out during one calendar month of liquids collecting within the bunds - within two weeks following the end of that calendar month;
- (ii) removals of water and other liquids during a calendar month - within two weeks following the end of that calendar month.

I4 Monitoring of Surface Water Arisings

(a) Surface Water Monitoring Programme:

No waste shall be received on the site until a surface water monitoring programme has been submitted in writing to and agreed in writing by, the Waste Regulation Authority and until this agreed programme has been incorporated in the Working Plan. This programme shall specify the following:

- (i) the frequency at which conductivity measurements of surface water arising from the site and in watercourses adjacent to the site shall be carried out at specified locations on or adjacent to the site, which shall be in accordance with the minimum frequency specified in Annex D to this licence;
- (ii) the frequency at which samples of surface water arising from the site and in watercourses adjacent to the site shall be taken from specified locations on or adjacent to the site, which shall be in accordance with the minimum frequency specified in Annex D to this licence;
- (iii) the list of parameters for which such samples of surface water shall be analysed, which shall be in accordance with the list contained in Annex D to this licence, unless otherwise agreed in writing with the Waste Regulation Authority and specified in the Working Plan;
- (iv) the methods of analysis by which such samples shall be analysed, which shall be in accordance with the methods specified in Annex D to this licence, unless otherwise agreed in writing with the Waste Regulation Authority and specified in the Working Plan;
- (v) the form in which the results of such conductivity measurements and analyses shall be recorded.

(b) Initial Measurements:

No waste shall be deposited on the site until initial conductivity measurements and analyses of samples of surface water arising from the site and in watercourses adjacent to the site have been carried out at the locations specified in the Working Plan in accordance with Condition I4(a) above.

(c) Recording of Surface Water Monitoring Results:

All results of conductivity measurements and analyses of samples of surface water carried out in accordance with Condition I4(a) and I4(b) shall be recorded in accordance with Conditions D1 and I4(a).

(d) Retention of Records:

All records made in accordance with the requirements of Condition I4(c) shall be kept in accordance with the requirements of Condition D2.

(e) Submission of Copies of Monitoring Records to the Waste Regulation Authority:

A copy of the records made in accordance with the requirements of Condition I4(c) shall be submitted in writing to the Waste Regulation Authority as follows:

- (i) conductivity measurements taken during one calendar month - within two weeks following the end of that calendar month;
- (ii) each analysis of a sample - within one calendar month of the sample being taken.

(f) Revisions to the Surface Water Monitoring Programme:

If it becomes apparent that the frequencies of carrying out conductivity measurements, sampling and analysis has become inappropriate they shall only be changed by revision of the Working Plan which has been approved in writing by the Waste Regulation Authority in accordance with Condition A8.

(g) Trigger Levels:

The trigger levels for each of the parameters specified in the monitoring programme shall be ten times the background level for that parameter as determined by the initial measurements, unless otherwise specified in writing by the Waste Regulation Authority.

In the event of the trigger level for a parameter being exceeded the Waste Regulation Authority and the National Rivers Authority shall be notified immediately, and measures as specified in the Working Plan shall be put into immediate effect to identify the cause of the trigger level being exceeded and to remedy the situation.

I5 Monitoring of Groundwater

Unless specifically agreed in writing by the Waste Regulation Authority and specified in the Working Plan, the following Conditions I5(a) to I5(g) shall apply to the site and shall be carried out:

(a) Groundwater Monitoring Programme:

No waste shall be received on the site until a groundwater monitoring programme has been submitted in writing to, and agreed in writing by, the Waste Regulation Authority, and until this agreed programme has been incorporated in the Working Plan. This programme shall specify the following:

- (i) the frequency at which conductivity measurements of groundwater in the vicinity of the site shall be carried out at specified locations on or adjacent to the site, which shall be in accordance with the minimum frequency specified in Annex D to this licence;
- (ii) the frequency at which samples of groundwater in the vicinity of the site shall be taken from specified locations on or adjacent to the site, which shall be in accordance with the minimum frequency specified in Annex D to this licence;

- (iii) the list of parameters for which such samples of groundwater shall be analysed which shall be in accordance with Annex D of this licence, unless otherwise agreed in writing with the Waste Regulation Authority and specified in the Working Plan;
 - (iv) the methods of analysis by which such samples shall be analysed, which shall be in accordance with the methods specified in Annex D to this licence, unless otherwise agreed in writing with the Waste Regulation Authority and specified in the Working Plan;
 - (v) the form in which the results of such conductivity measurements and analyses shall be recorded.
- (b) Initial Measurements:**
- No waste shall be deposited on the site until initial conductivity measurements and analyses of samples of groundwater in the vicinity of the site have been carried out at the locations specified in the Working Plan in accordance with Condition I5(a) above.
- (c) Recording of Groundwater Monitoring Results:**
- All results of conductivity measurements and analyses of samples of groundwater carried out in accordance with Condition I5(a) and I5(b) shall be recorded in accordance with Conditions D1 and I5(a).
- (d) Retention of Records:**
- All records made in accordance with the requirements of Condition I5(c) shall be kept in accordance with the requirements of Condition D2.
- (e) Submission of Copies of Monitoring Records to the Waste Regulation Authority:**
- A copy of the records made in accordance with the requirements of Condition I5(c) shall be submitted in writing to the Waste Regulation Authority as follows:
- (i) each conductivity measurement - within one week of the measurement being taken;
 - (ii) each analysis of a sample - within one calendar month of the sample being taken.
- (f) Revisions to the Groundwater Monitoring Programme:**
- If it becomes apparent that the frequencies of carrying out conductivity measurements, sampling and analysis has become inappropriate they shall only be changed by revision of the Working Plan which has been approved in writing by the Waste Regulation Authority, in accordance with Condition A8.
- (g) Trigger Levels:**
- The trigger levels for each of the parameters specified in the monitoring programme shall be ten times the background level for that parameter as determined by the initial measurements, unless otherwise specified in writing by the Waste Regulation Authority.

In the event of the trigger level for a parameter being exceeded the Waste Regulation Authority and the National Rivers Authority shall be notified immediately, and measures as specified in the Working Plan shall be put into immediate effect to identify the cause of the trigger level being exceeded and to remedy the situation.

I6 Control of Aerial Emissions from the Site

Any aerial emission from the site shall be so treated or arrested that it does not exceed one fortieth of the relevant Occupational Exposure Level at hospitals, schools, and premises where persons reside in the vicinity of the site; and does not exceed the Occupational Exposure Limit at other industrial or commercial developments in the vicinity of the site. The methods adopted to treat or arrest emissions in order to achieve this shall be specified in the Working Plan.

J SITE PREPARATION AND MAINTENANCE

J1 Preparation and Maintenance of Site Surface

No waste shall be deposited on the site until the surface of the site has been covered with a suitable impervious concrete surface as specified in the Working Plan. This surface shall be maintained at all times in a state of good repair.

J2 Surface Water Drainage and Monitoring Systems

The following surface water drainage and monitoring systems shall be provided as specified in the Working Plan and in accordance with Condition G1:

- (a) surface water drainage, collection and discharge system incorporating a suitable interceptor or catchpit prior to discharge;
- (b) marked surface water monitoring points in watercourses on or adjacent to the site.

J3 Groundwater Monitoring Systems

Unless specifically agreed in writing with the Waste Regulation Authority in accordance with Condition I5, the following groundwater monitoring systems shall be provided as specified in the Working Plan and in accordance with Condition G1:

- (a) groundwater monitoring boreholes;
- (b) groundwater monitoring points.

J4 Construction of Bays

No waste shall be received at the site until storage bays have been constructed and marked out using white painted lines as agreed in the Working Plan.

No Special Waste shall be received at the site until the bunded Special Waste storage bay has been constructed as agreed in the Working Plan.

No waste shall be received at the site until the drainage system with interceptor points has been completed in such a manner that all surface water drainage from the bay areas shall be directed to drainage via interceptor points, as specified in Condition J2(a).

No Special Waste shall be received at the site until the Special Waste storage bay has been constructed in such a manner that all drainage from the bay is directed to the interceptor point as specified in Condition J2(a).

J5 Construction of Bunds

No waste in liquid or sludge form shall be received at the site until impervious bunds have been constructed in accordance with Condition G8 of this licence. The location, capacity and structure of these bunds must be agreed in writing with the Waste Regulation Authority and this information must be incorporated into the Working Plan.

J6 Maintenance of Site

The reception and storage areas, drain system, gullies and interceptor pit shall be maintained at all times in a state of good repair. The storage bays and bund shall be checked daily and all necessary maintenance carried out at the earliest opportunity. The white-coloured painted lines specified for each bay in Condition J4 shall remain clearly visible at all times.

GROUP 1

ANNEX A : PERMITTED WASTE TYPES (CONDITIONS B1 AND B2)

MAXIMUM TOTAL DAILY INPUT OF GROUP 1 WASTES: NOT EXCEEDING 280 TONNES/DAY
MAXIMUM DAILY INPUT OF EACH WASTE TYPE FROM GROUP 1: AS SPECIFIED BELOW (CONDITION B1(b))

NOTE: MAXIMUM TOTAL DAILY INPUT OF ALL PERMITTED WASTES TO ENTIRE SITE IS 280 TONNES/DAY

CONTAMINATION LEVELS:
THE MAXIMUM PERMITTED CONTAMINATION LEVELS FOR WASTE TYPES IN THIS GROUP OF THOSE CONTAMINANTS SPECIFIED IN ANNEX B ARE THE MAXIMUM LEVELS FOR SOIL CLASS A.

THE WASTE TYPES PERMITTED FROM GROUP 1 AND THE MAXIMUM WEEKLY INPUT EXPRESSED AS A PROPORTION OF THE TOTAL WEEKLY INPUT OF GROUP 1 WASTES TO THE SITE ARE AS FOLLOWS:-

GROUP 1 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% v/v total weekly actual intake of group 1 wastes to site)	CONDITIONS/COMMENTS
SOIL CLASS A (UNCONTAMINATED SOIL)		100%	
UNCONTAMINATED RUBBLE/HARDCORE		100%	
STONE		100%	
CLAY		100%	
SAND (EXCEPT POUNDRY SAND)		100%	
SILICA, CARBON, KIRSCHLAGER (EXCEPT WHERE USED AS FILTER MATERIAL)		100%	
GLASS, POTTERY, CHINA, FIRED ENAMELS, CERAMICS, MICA		100%	
BRICKWORK		100%	
CONCRETE		100%	
BOILER SCALE		NOT PERMITTED	
WEATHERED TAR/BITUMEN AGGREGATE		100%	
SLAG, ASH, CLINKER (EXCEPT INCINERATOR RESIDUE)		NOT PERMITTED	
MINERAL PROCESSING WASTES		100%	

GROUP 1 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 1 wastes to site)	CONDITIONS/COMMENTS
MIXED WASTES (GROUP 1) (as follows): MIXED PERMITTED WASTE TYPES FROM GROUP 1 ONLY		100%	

RD/LIC/255/82/M3
TS2RBV1

GROUP 2

ANNEX A CONTINUED....PERMITTED WASTE TYPES (CONDITIONS B1 AND B2)

MAXIMUM TOTAL DAILY INPUT OF GROUP 2 WASTES: NOT EXCEEDING 280 TONNES/DAY
MAXIMUM DAILY INPUT OF EACH WASTE TYPE FROM GROUP 2: AS SPECIFIED BELOW (CONDITION B1(b))

NOTE: MAXIMUM TOTAL DAILY INPUT OF ALL PERMITTED WASTES TO ENTIRE SITE IS 280 TONNES/DAY

CONTAMINATION LEVELS:
THE MAXIMUM PERMITTED CONTAMINATION LEVELS FOR WASTE TYPES IN THIS GROUP OF THOSE CONTAMINANTS SPECIFIED IN ANNEX B ARE THE MAXIMUM LEVELS FOR SOIL CLASS B.

THE WASTE TYPES PERMITTED FROM GROUP 2 AND THE MAXIMUM WEEKLY INPUT EXPRESSED AS A PROPORTION OF THE TOTAL WEEKLY INPUT OF GROUP 2 WASTES TO THE SITE ARE AS FOLLOWS:-

GROUP 2 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 2 wastes to site)	CONDITIONS/COMMENTS
WOOD - TREATED TIMBER		100%	
WOOD - UNTREATED TIMBER		100%	
WOOD PRODUCTS - HARDBOARD, GIBBOARD		100%	
SAND/ST/BANDERDUST		100%	
TREES, BUSHES, TREE/HEDGE CUTTINGS		100%	
PAPER, INCLUDING OILED/TARRED PAPER		100%	
CARDBOARD, FIBREBOARD		100%	
COKE, ESOMITE, KAPOK		100%	
PLASTIC		100%	
TANNED LEATHER		100%	
TEXTILES/FIBRES - NATURAL OR MAN-MADE		100%	
(Group 2 Wastes Continued...)			

GROUP 2 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% v/v total weekly actual intake of Group 2 wastes to site)	CONDITIONS/COMMENTS
CEMENT (EXCEPT AS CONSTITUENT OF BRICKWORK OR CONCRETE)		100%	
CONTAMINATED WASTES (GROUP 2) (as follows): WASTE TYPES OTHERWISE PERMITTED FROM GROUP 1 OR GROUP 4 WITH CONTAMINATION LEVELS EXCEEDING THOSE SPECIFIED FOR SOIL CLASS A IN ANNEX B BUT WITHIN THOSE SPECIFIED FOR SOIL CLASS B		100%	
CONTAMINATED SOIL (as follows): SOIL CLASS B (SLIGHTLY CONTAMINATED SOIL)		100%	Contamination levels defined in Annex B. Requires analysis.
MIXED WASTES (GROUP 2) (as follows): MIXED PERMITTED WASTE TYPES FROM GROUP 2 ONLY MIXED PERMITTED WASTE TYPES FROM GROUP 1 AND 2		100% 100% 100%	

GROUP 3

ANNEX A CONTINUED.....PERMITTED WASTE TYPES (CONDITIONS B1 AND B2)

MAXIMUM TOTAL DAILY INPUT OF GROUP 3 WASTES: NOT EXCEEDING 280 TONNES/DAY
MAXIMUM DAILY INPUT OF EACH WASTE TYPE FROM GROUP 3: AS SPECIFIED BELOW (CONDITION B1(b))

NOTE: MAXIMUM TOTAL DAILY INPUT OF ALL PERMITTED WASTES TO ENTIRE SITE IS 280 TONNES/DAY

CONTAMINATION LEVELS:
THE MAXIMUM PERMITTED CONTAMINATION LEVELS FOR WASTE TYPES IN THIS GROUP OF THOSE CONTAMINANTS SPECIFIED IN ANNEX B ARE THE MAXIMUM LEVELS FOR SOIL CLASS C.

THE WASTE TYPES PERMITTED FROM GROUP 3 AND THE MAXIMUM WEEKLY INPUT EXPRESSED AS A PROPORTION OF THE TOTAL WEEKLY INPUT OF GROUP 3 WASTES TO THE SITE ARE AS FOLLOWS:-

GROUP 3 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of group 3 wastes to site)	CONDITIONS/COMMENTS
HOUSEHOLD WASTE/REFUSE - TREATED OR UNTREATED		10%	As inherent component of skip waste
COMMERCIAL REFUSE (CONSISTING OF PAPER, CARDBOARD, PLASTIC, WOOD)		100%	
EMPTY USED CONTAINERS (CONSTRUCTED OF METAL, GLASS, PLASTIC, PAPER, CARDBOARD, WOOD, ETC.)		100%	
SCRAP MACHINERY/EQUIPMENT - PERIOUS		100%	
SCRAP MACHINERY/EQUIPMENT - NON-PERIOUS		100%	
ELECTRICAL FITTINGS/FIXTURES/APPLIANCES		100%	
VEGETABLE MATTER (OTHER THAN TREES, BUSHES, TREE/HEDGE CLIPPINGS)		20%	
WASTE FOOD OR FOOD PROCESSING MATERIALS		20%	
(Group 3 Wastes Continued)			

GROUP 3 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/v total weekly actual intake of Group 3 wastes to site)	CONDITIONS/COMMENTS
ANIMAL CARCASSES OR PARTS THEREOF		NOT PERMITTED	
CLINICAL WASTES - TREATED OR UNTREATED		NOT PERMITTED	
RUBBER (INCLUDING TYRES)		100%	
SOAP		10%	
DETERGENTS		10%	
COSMETIC PRODUCTS - RETAIL ONLY		10%	
DRY SEWAGE SLUDGE		NOT PERMITTED	
INCINERATOR RESIDUE		NOT PERMITTED	
FOUNDRY SAND		0.5%	
PLASTER		10%	
PLASTERBOARD		100%	
CONTAMINATED WASTES (GROUP 3) (as follows): WASTE TYPES OTHERWISE PERMITTED FROM GROUP 1, GROUP 2 OR GROUP 4 WITH CONTAMINATION LEVELS EXCEEDING THOSE SPECIFIED IN ANNEX B FOR SOIL CLASS B, BUT WITHIN THOSE FOR SOIL CLASS C.		10%	Require analysis
CONTAMINATED SOIL (as follows): SOIL CLASS C (CONTAMINATED SOIL)		10%	Require analysis
(Group 3 Wastes Continued....)			

GROUP 4

ANNEX A CONTINUED.....PERMITTED WASTE TYPES (CONDITIONS B1 AND B2)

MAXIMUM TOTAL DAILY INPUT OF GROUP 4 WASTES: NOT EXCEEDING 250 TONNES/DAY
MAXIMUM DAILY INPUT OF EACH WASTE TYPE FROM GROUP 4: AS SPECIFIED BELOW (CONDITION B1(b))

NOTE: MAXIMUM TOTAL DAILY INPUT OF ALL PERMITTED WASTES TO ENTIRE SITE IS 280 TONNES/DAY

CONTAMINATION LEVELS:

THE MAXIMUM PERMITTED CONTAMINATION LEVELS FOR WASTE TYPES IN THIS GROUP OF THOSE CONTAMINANTS SPECIFIED IN ANNEX B ARE THE MAXIMUM LEVELS FOR SOIL CLASS A.

THE WASTE TYPES PERMITTED FROM GROUP 4 AND THE MAXIMUM WEEKLY INPUT EXPRESSED AS A PROPORTION OF THE TOTAL WEEKLY INPUT OF GROUP 4 WASTES TO THE SITE ARE AS FOLLOWS:-

GROUP 4 WASTE TYPES (Solids only permitted)	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 4 wastes to site)	CONDITIONS/COMMENTS
ASBESTOS LAGGING - ALL FORMS		2.5%	
ASBESTOS FIBRE/POWDER		2.5%	
ASBESTOS SHEET/PIPING, COMPOSITE/BONDED		10%	
MIXED WASTES (GROUP 4) (as follows):			
MIXED PERMITTED WASTE TYPES FROM GROUP 4 ONLY		2.5%	
MIXED PERMITTED WASTE TYPES FROM GROUP 1 AND/OR GROUP 2 AND/OR GROUP 3 AND GROUP 4		100%	Provided proportion of each particular waste type does not exceed maximum permitted weekly % for that waste type. Asbestos waste must be inherently component of mixed wastes and must not exceed 2.5% w/w of mixture.

GROUP 5

ANNEX A CONTINUED.....PERMITTED WASTE TYPES (CONDITIONS B1 AND B2)

MAXIMUM TOTAL DAILY INPUT OF GROUP 5 WASTES: NOT EXCEEDING 60 TONNES/DAY
MAXIMUM TOTAL DAILY INPUT OF EACH TYPE FROM GROUP 5 AS SPECIFIED BELOW (CONDITION B1(b))

NOTE: MAXIMUM TOTAL DAILY INPUT OF ALL PERMITTED WASTES TO ENTIRE SITE IS 280 TONNES/DAY

CONTAMINATION LEVELS:
THE MAXIMUM PERMITTED CONTAMINATION LEVELS FOR WASTE TYPES IN THIS GROUP OF THOSE CONTAMINANTS SPECIFIED IN ANNEX B ARE THE
MAXIMUM LEVELS FOR SOIL CLASS E.

THE WASTE TYPES PERMITTED FROM GROUP 5 AND THE MAXIMUM WEEKLY INPUT EXPRESSED AS A PROPORTION OF THE TOTAL WEEKLY INPUT OF GROUP 5 WASTES
TO THE SITE ARE AS FOLLOWS:-

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
<u>INORGANIC ACIDS:</u>			
pH < 4.0		NOT PERMITTED	
pH > 4.0, EXCEPT WHERE SPECIFICALLY PERMITTED UNDER OTHER WASTE TYPES IN GROUPS 1 TO 5		NOT PERMITTED	
<u>ORGANIC ACIDS AND RELATED COMPOUNDS:</u>			
pH < 4.0		NOT PERMITTED	
pH > 4.0, EXCEPT WHERE SPECIFICALLY PERMITTED UNDER OTHER WASTE TYPES IN GROUPS 1 TO 5		NOT PERMITTED	
<u>ALKALIS:</u>			
pH > 9.0		NOT PERMITTED	
pH < 9.0, AS FOLLOWS:		NOT PERMITTED	
HYDROXIDES OF SODIUM, POTASSIUM OR CALCIUM		NOT PERMITTED	
OXIDES OF SODIUM, POTASSIUM OR CALCIUM		NOT PERMITTED	
(Group 5 Wastes Continued...)			

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
CARBONATES OF SODIUM, POTASSIUM OR CALCIUM		NOT PERMITTED	
AMMONIA		NOT PERMITTED	
PROPRIETARY ALKALINE CLEANERS		NOT PERMITTED	
ALKALI METAL PHOSPHATES		NOT PERMITTED	
METALS AND INORGANIC METAL COMPOUNDS (except where specifically addressed under other waste types in Groups 1 to 5) (as follows):			
ALUMINIUM		NOT PERMITTED	
ALUMINIUM COMPOUNDS		NOT PERMITTED	
BARIUM AND BARIUM COMPOUNDS		NOT PERMITTED	
BERYLLIUM AND BERYLLIUM COMPOUNDS		NOT PERMITTED	
BORON AND BORON COMPOUNDS		NOT PERMITTED	
CADMIUM AND CADMIUM COMPOUNDS		NOT PERMITTED	
CALCIUM AND CALCIUM COMPOUNDS		NOT PERMITTED	
CERBIUM		NOT PERMITTED	
CERONIUM COMPOUNDS		NOT PERMITTED	
COBALT AND COBALT COMPOUNDS		NOT PERMITTED	
COPPER		NOT PERMITTED	
COPPER COMPOUNDS		NOT PERMITTED	
IRON AND IRON COMPOUNDS		NOT PERMITTED	
(Group 5 Wastes Continued...)			

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
LEAD AND LEAD COMPOUNDS MAGNESIUM AND MAGNESIUM COMPOUNDS MERCURY AND MERCURY COMPOUNDS MOLYBDENUM AND MOLYBDENUM COMPOUNDS NICKEL AND NICKEL COMPOUNDS OSMIUM AND OSMIUM COMPOUNDS PHOSPHORUS PHOSPHORUS COMPOUNDS POTASSIUM AND POTASSIUM COMPOUNDS SILVER AND SILVER COMPOUNDS SODIUM SODIUM COMPOUNDS TANTALUM AND TANTALUM COMPOUNDS TIN AND TIN COMPOUNDS TITANIUM AND TITANIUM COMPOUNDS TUNGSTEN AND TUNGSTEN COMPOUNDS ZINC AND ZINC COMPOUNDS ZIRCONIUM AND ZIRCONIUM COMPOUNDS		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
(Group 5 Wastes Continued...)			

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
METALLOID ELEMENTS AND COMPOUNDS (except where specifically addressed under other waste types in Groups 1 to 5) (as follows):			
ANTIMONY AND ANTIMONY COMPOUNDS		NOT PERMITTED	
ARSENIC AND ARSENIC COMPOUNDS		NOT PERMITTED	
BISMUTH AND BISMUTH COMPOUNDS		NOT PERMITTED	
SELENIUM AND SELENIUM COMPOUNDS		NOT PERMITTED	
TELLURIUM AND TELLURIUM COMPOUNDS		NOT PERMITTED	
ORGANIC COMPOUNDS (except where specifically addressed under other waste types in Groups 1 to 5) (as follows):			
ORGANOHALOGEN COMPOUNDS		NOT PERMITTED	
ORGANO-METALLIC COMPOUNDS		NOT PERMITTED	
ORGANO-NITROGEN COMPOUNDS		NOT PERMITTED	
ORGANO-SULPHUR COMPOUNDS		NOT PERMITTED	
ORGANO-PHOSPHORUS COMPOUNDS		NOT PERMITTED	
PEROXIDES, ANALOGUES AND DERIVATIVES		NOT PERMITTED	
PEROXIDES		NOT PERMITTED	
CHELATING COMPOUNDS		NOT PERMITTED	
PTERIDINES		NOT PERMITTED	
SOLVENTS		NOT PERMITTED	
(Group 5 Wastes Continued...)			

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
THINNERS		NOT PERMITTED	
MIXED SOLVENTS AND THINNERS		NOT PERMITTED	
PETROL, KEROSENE, DERV, FUEL OIL		NOT PERMITTED	
OTHER COMPOUNDS (INORGANIC OR ORGANIC) (except where specifically addressed under other waste types in Groups 1 to 5) (as follows):			
CYANIDES (ALL TYPES)		NOT PERMITTED	
SULFIDES		NOT PERMITTED	
SELENIDES		NOT PERMITTED	
TELLURIDES		NOT PERMITTED	
ARSENIDES		NOT PERMITTED	
OXIDISING COMPOUNDS		NOT PERMITTED	
CARBIDES AND ACETYLIDES		NOT PERMITTED	
POLYMERIC MATERIALS (except where specifically addressed under other waste types in Groups 1 to 5) (as follows):			
PRECURSORS, MONOMERS AND PRODUCTS OF INCOMPLETE POLYMERIZATION		20%	
FINISHED PRODUCTS AND MANUFACTURING SCRAPS		20%	
SCRAP RUBBER (EXCLUDING TYRES)		5%	
LATEX, LATEX/RUBBER SOLUTIONS/SUSPENSIONS		15%	
SYNTHETIC ABRASIVE WASTES		15%	
(Group 5 Wastes Continued...)			

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% v/v total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
ION EXCHANGE RESIN WASTES		NOT PERMITTED	
FINE CHEMICALS:			
PHARMACEUTICALS		10%	
COSEMETIC PRODUCTS		15%	
BIOCIDES, ETC:			
BIOCIDES		NOT PERMITTED	
PESTICIDES		NOT PERMITTED	
HERBICIDES		NOT PERMITTED	
FUNGICIDES		NOT PERMITTED	
MISCELLANEOUS CHEMICAL WASTES (except where specifically addressed under other waste types in groups 1 to 5) (as follows):			
MIXED ORGANIC COMPOUNDS		NOT PERMITTED	
MIXED INORGANIC COMPOUNDS		NOT PERMITTED	
LABORATORY CHEMICALS		NOT PERMITTED	
UNIDENTIFIED CHEMICALS		NOT PERMITTED	
ORGANICS IDENTIFIED BY TRADE NAME ONLY		NOT PERMITTED	
INORGANICS IDENTIFIED BY TRADE NAME ONLY		2.5%	
FILTER MATERIALS, CONTAMINATED RUBBISH AND TREATMENT SLUDGE:			
USED FILTER MATERIALS (INCLUDING CARBON, Kieselguhr)		15%	
(Group 5 Wastes Continued...)			

GROUP 5 WASTE TYPES (Solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
CONTAMINATED RUBBISH (BAGS, SACKS, CONTAINERS) PCB CONTAMINATED ITEMS INDUSTRIAL EFFLUENT TREATMENT SLUDGE FILTER SCREENINGS	20%		
	NOT PERMITTED	5%	
		2.5%	
INTERCEPTOR WASTES, TARS, PAINTS, DYES AND PIGMENTS: TANK CLEANING SLUDGE INTERCEPTOR PIT WASTES	NOT PERMITTED		
	NOT PERMITTED	50%	
		50%	
PAINT/VARNISH WASTES (MANUFACTURE/USE) DYE/STUFFS WASTE DISTILLATION RESIDUES		15%	
	NOT PERMITTED		
		5%	
TAR, PITCH, BITUMEN AND ASPHALTS (EXCEPT AS WEATHERED TAR/BITUMEN AGGREGATE) ACID TARS		NOT PERMITTED	
		NOT PERMITTED	
		NOT PERMITTED	
CONTAMINATED WASTES (GROUP 5) (as follows): WASTE TYPES OTHERWISE PERMITTED FROM GROUPS 1 TO 5 WITH CONTAMINATION LEVELS EXCEEDING THOSE SPECIFIED IN ANNEX B FOR SOIL CLASS C, BUT WITHIN THOSE SPECIFIED FOR SOIL CLASS D CONTAMINATED SOILS (as follows): SOIL CLASS D (HEAVILY CONTAMINATED SOIL)			
		NOT PERMITTED	Contamination levels defined in Annex B.
(Group 5 Wastes Continued....)			

GROUP 5 WASTE TYPES (solids only permitted, except where specifically permitted as liquid or sludge under "Conditions/Comments")	CODE	MAXIMUM PERMITTED WEEKLY QUANTITY (% w/w total weekly actual intake of Group 5 wastes to site)	CONDITIONS/COMMENTS
SOIL CLASS E (UNUSUALLY HEAVILY CONTAMINATED SOIL)		NOT PERMITTED	Contamination levels defined in Annex B.
MIXED WASTES (GROUP 5) (except where specifically addressed under other waste types in Group 5) (as follows):			
MIXED PERMITTED WASTE TYPES FROM GROUP 5 ONLY		10%	
MIXED PERMITTED WASTE TYPES FROM GROUP 1 AND/OR GROUP 2 AND/OR GROUP 3 AND/OR GROUP 4 AND GROUP 5		NOT PERMITTED	

ANNEX B : SOIL CLASSES A TO E - LIMITS OF RANGES FOR CONTAMINATION LEVELS

RANGES OF PERMITTED CONTAMINATION (mg/kg on air dried soils, except for pH)

Symbol	PARAMETER/CONTAMINANT	SOIL CLASS A		SOIL CLASS B		SOIL CLASS C		SOIL CLASS D		SOIL CLASS E	
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
	pH (acid)	6	7	5	6	4	5	2	4	2	
	pH (alkali)	7	8	8	9	9	10	10	12	12	
Sb	Antimony	0	30	30	50	50	100	100	500	500	500
As	Arsenic	0	30	30	50	50	100	100	500	500	500
Cd	Cadmium	0	1	1	3	3	10	10	50	50	50
Cr	Chromium	0	100	100	200	200	500	500	2,500	2,500	2,500
Cu	Copper (available)	0	100	100	200	200	500	500	2,500	2,500	2,500
Pb	Lead (total)	0	500	500	1,000	1,000	2,000	2,000	10,000	10,000	10,000
	Lead (available)	0	200	200	500	500	1,000	1,000	5,000	5,000	5,000
Hg	Mercury	0	1	1	3	3	10	10	50	50	50
Ni	Nickel (available)	0	20	20	50	50	200	200	1,000	1,000	1,000
Zn	Zinc (available)	0	250	250	500	500	1,000	1,000	5,000	5,000	5,000
	Zinc equivalent	0	250	250	500	500	2,000	2,000	10,000	10,000	10,000
B	Boron (available)	0	2	2	5	5	50	50	250	250	250
Se	Selenium	0	1	1	3	3	10	10	50	50	50
Ba	Barium	0	500	500	1,000	1,000	2,000	2,000	10,000	10,000	10,000
Be	Beryllium	0	5	5	10	10	20	20	50	50	50
Mn	Manganese	0	500	500	1,000	1,000	2,000	2,000	10,000	10,000	10,000
V	Vanadium	0	100	100	200	200	500	500	2,500	2,500	2,500
Mg	Magnesium	0	500	500	1,000	1,000	2,000	2,000	10,000	10,000	10,000
SO ₄	Sulphate	0	2,000	2,000	5,000	5,000	10,000	10,000	50,000	50,000	50,000
S	Sulphur (free)	0	100	100	500	500	1,000	1,000	5,000	5,000	5,000
	Sulphide	0	10	10	20	20	100	100	500	500	500
CN	Cyanide (free)	0	1	1	5	5	50	50	100	100	100
	Cyanide (total)	0	5	5	25	25	250	250	500	500	500
	Pericyanide	0	100	100	500	500	1,000	1,000	5,000	5,000	5,000
	Thiocyanate	0	10	10	50	50	100	100	500	500	500
	Coal Tar	0	500	500	1,000	1,000	2,000	2,000	10,000	10,000	10,000
	Phenols	0	1	1	5	5	50	50	250	250	250
	Toluene extract	0	5,000	5,000	10,000	10,000	50,000	50,000	250,000	250,000	250,000
	Cyclohexane extract	0	2,000	2,000	5,000	5,000	20,000	20,000	100,000	100,000	100,000
PCB	Polychlorinated biphenyls	0	1	1	3	3	10	10	50	50	50
	Polycyclic aromatic hydrocarbons	0	50	50	500	500	1,000	1,000	5,000	5,000	5,000
	Chlorinated solvents	0	1	1	3	3	10	10	50	50	50

Continued....

ANNEX B CONTINUED.... : SOIL CLASSES A TO E - LIMITS OF RANGES FOR CONTAMINATION LEVELS

NOTES:

- (1) Soil Classes: Soil Class A: Uncontaminated soil
Soil Class B: Slightly contaminated soil
Soil Class C: Contaminated soil
Soil Class D: Heavily contaminated soil
Soil Class E: Unusually heavily contaminated soil
- (2) In the event of a measured contamination level falling exactly on the boundary of two soil classes, the upper (more heavily contaminated) soil class should be assumed.
- (3) Only Soil Class A can be disposed of at an inert landfill site.
Soil Classes B, C, D and E, must be disposed of at a suitably licensed landfill site.
- (4) In the cases of Soil Class D (heavily contaminated soil) and Soil Class E (unusually heavily contaminated soil) an analysis must be carried out to determine whether the soil is a Special Waste and, if so, the disposal carried out in accordance with the requirements of the "Control of Pollution (Special Waste) Regulations 1980".
- (5) Unless specifically stated otherwise, contamination levels are for total concentration of contaminant, extractable by $\text{HClO}_3/\text{HClO}_4$ (ICRCL Guidance Note 59/83 Second Edition).
- (6) Available concentration of contaminant determined by standard ADAS method (soluble in hot water) (ICRCL Guidance Note 59/83, Second Edition).
- (7) Zinc equivalent: Combination of copper, nickel and zinc.
- (8) For contaminants not listed it must be assumed that the soil is not permitted (unless specifically permitted under Condition B1 and Annex A).

ANNEX C: ANALYSIS OF SAMPLES OF WASTE

1. TESTS AND METHODS OF ANALYSIS

Unless otherwise specifically agreed in writing with the Waste Regulation Authority and specified in detail in the Working Plan, the following tests and methods of analysis shall be used in any analyses of wastes carried out in accordance with Conditions C1(b), D1(c) and D3(c) of this licence.

PARAMETER	FULL ANALYSIS	SOIL ANALYSIS	REFERENCE METHOD
pH	Standard Reference Electrode adjusted to 25°C	Standard Reference Electrode adjusted to 25°C	
ACID/ALKALI STRENGTH	Titrimetric Analysis		
FLAMMABILITY			
FLASHPOINT	Closed cup method (Seta-Flash)		
SPECIFIC GRAVITY	Hydrometer at 15.5°C		
REACTIVITY/ COMPATIBILITY WITH: (a) ACIDS (b) ALKALIS (c) WATER (d) OTHER SUBSTANCES RELEVANT TO WASTE TYPE	Test exothermic reaction leading to temperature rise (°C).		
	Test release of noxious gases using Draeger tubes.		
APPEARANCE/ODOUR	Observe: (a) No of phases (liquids). (b) Homogeneity (solids). (c) Presence of: (i) Toxic vapours; (ii) Noxious vapours/odours; (iii) Slight odours.		
COMPONENTS - HEAVY METALS, ETC	Atomic Absorption Spectrophotometer (AAS) OR Mass Spectrophotometer (MS) OR Gas Liquid Chromatography (GLC)	As per Annex B	

Continued...

2. LEACHATE TEST FOR ANALYSIS OF SOLID WASTES

Where the waste being tested is in solid form and the relevant test is required to be carried out on a liquid, the method to be used will be the proposed "ASTM Leaching of Waste Materials Test" as specified in the National Sanitation Foundation Report on Leachate Testing of Hazardous Chemicals from Stabilised Automotive Wastes (January 1979), subject to the following modifications.

2.1 Method

A distilled water-shake extraction procedure shall be used.

2.2 Procedure

2.2.1 Shake Procedure

- (a) A sample of 500g of waste material which shall be representative of the whole contents of the load shall be taken. The sample shall be ground, coned and quartered to obtain a representative sample of 150g of material passing a 1mm sieve. Any material not passing the specified sieve shall be retained and may be separately examined.
- (b) Use approximately 100g of the ground material, and determine and record the weight of the sample used to an accuracy of $\pm 1g$.
- (c) Add a volume of test water equal in millilitres to four times the weight in grams of the sample used in (b).

2.3 Analysis

2.3.1 The aqueous filtrate shall be analysed for specified parameters using the specified analytical methods as defined in the above table (or such recognised similar tests producing equivalent results as may have been previously agreed in writing with the Waste Regulation Authority and specified in the Working Plan).

2.3.2 Where non-aqueous liquid is present it shall be separately analysed as specified in 2.3.1.

2.4 Calculation of Results

2.4.1 All results shall be reported in terms of milligrams per litre of filtrate.

ANNEX D : ANALYSIS OF SAMPLES OF (a) SURFACE WATER, (b) GROUNDWATER					
PARAMETER	UNITS	FREQUENCY OF SAMPLING AND ANALYSIS PER SAMPLING POINT		BLUE BOOK NUMBER	METHOD TITLE AND YEAR
		SURFACE WATER (a) Discharge from site (b) Perimeter ditches	GROUNDWATER		
Conductivity	us/cm	Daily	Quarterly	13	The Measurement of Electrical Conductivity and Laboratory Determination of the pH value of Natural, Treated and Waste Waters (1978).
pH Value	-	Quarterly	Quarterly	13	The Measurement of Electrical Conductivity and Laboratory Determination of the pH value of Natural, Treated and Waste Waters (1978).
COD (Chemical Oxygen Demand)	mg/l	Quarterly	Quarterly	3	Chemical Oxygen Demand of Polluted and Waste Waters (1977).
Ammoniacal nitrogen	mg/l	Quarterly	Quarterly	47	Ammonia in Waters (1980).
Nitrate nitrogen	mg/l	Quarterly	Quarterly	47	Ammonia in Waters (1980).
Nitrite nitrogen	mg/l	Quarterly	Quarterly	47	Ammonia in Waters (1980).
o-Phosphate Chloride Sulphate	mg/l	Quarterly	Quarterly	38	Phosphorus in Waters by Atomic Spectroscopy (1980). Analysis of Raw, Potable and Waste Waters (1972). Analysis of Raw, Potable and Waste Waters (1972).
Sodium	mg/l	Quarterly	Quarterly	35	Sodium in Waters by Atomic Spectroscopy (1980).
Potassium	mg/l	Quarterly	Quarterly	36	Potassium in Waters by Atomic Spectroscopy (1980).
Magnesium	mg/l	Quarterly	Quarterly	7	Magnesium in Waters by Atomic Spectroscopy (1977).
Calcium	mg/l	Quarterly	Quarterly	8	Calcium in Waters by Atomic Spectroscopy (1977).
Chromium	mg/l	Quarterly	Quarterly	27	Chromium in Waters by Atomic Spectroscopy (1980).
Manganese	mg/l	Quarterly	Quarterly	10	Manganese in Waters by Atomic Spectroscopy (1977).
Iron	mg/l	Quarterly	Quarterly	9	Iron in Waters by Atomic Spectroscopy (1977).
Nickel	mg/l	Quarterly	Quarterly	46	Nickel in Waters by Atomic Spectroscopy (1981).
Copper	mg/l	Quarterly	Quarterly	31	Copper in Waters by Atomic Spectroscopy (1980).
Zinc	mg/l	Quarterly	Quarterly	32	Zinc in Waters by Atomic Spectroscopy (1980).
Cadmium	mg/l	Quarterly	Quarterly	2	Cadmium in Waters by Atomic Spectroscopy (1976).
Lead	mg/l	Quarterly	Quarterly	1	Lead in Waters by Atomic Spectroscopy (1976).
Mercury	mg/l	Quarterly	Quarterly	11	Mercury in Waters by Atomic Spectroscopy (1978).
Arsenic	mg/l	Quarterly	Quarterly	17	Arsenic in Waters by Atomic Spectroscopy (1978).
Total Cyanide	mg/l	Quarterly	Quarterly	50	Analysis of Raw, Potable and Waste Waters (1972).
Monohydric phenols	mg/l	Quarterly	Quarterly	50	Phenols in Waters and Effluents by GLC (1981).
Organochlorines	mg/l	Quarterly	Not Required	94	The Determination of Organochlorine Insecticides

ANNEX B: SCHEDULE OF SITE RECORDS

SUBJECT	RECORD	DETAILS	PARAMETERS	UNITS	FREQUENCY	SUBMISSION TO WRA		REF. COMD.
						FREQUENCY	DEADLINE	
WASTE INPUTS	RECORDS	TYPE OF WASTE	Annex A	TONNES	ONE/LOAD	ON REQUEST	ON REQUEST	D1(a)
		QUANTITY OF WASTE	WEIGHT					
		PERSON/COMPANY						
		SOURCE						
		TIME AND DATE						
		REGISTRATION NUMBER						
		DRIVER NAME						
		TYPES OF WASTE	Annex A		ONE/DAY	MONTHLY	WITHIN 10 WORKING DAYS FOLLOWING END OF WEEK	D1(a)
		TOTAL QUANTITY/TYPES	WEIGHT	TONNES				
		TYPE OF WASTE	Annex A	TONNES	ONE/LOAD	ON REQUEST	ON REQUEST	D1(b)
WASTE OUTPUTS	RECORDS	QUANTITY OF WASTE	WEIGHT					
		PERSON/COMPANY						
		DESTINATION						
		TIME AND DATE						
		REGISTRATION NUMBER						
		DRIVER NAME						
		TYPES OF WASTE	Annex A		ONE/DAY	MONTHLY	WITHIN 10 WORKING DAYS FOLLOWING END OF WEEK	D1(b)
		TOTAL QUANTITY/TYPES	WEIGHT	TONNES				
		DAILY SUMMARY						
		DAILY SUMMARY						

SUBJECT	RECORD	DETAILS	PARAMETERS	UNITS	FREQUENCY	SUBMISSION TO MRA		REF. COMDN.
						FREQUENCY	DEADLINE	
ANALYSES OF SOIL AND OTHER WASTE	SOIL CONTAMINATED ABOVE SOIL CLASS A	SOIL ANALYSIS	AS PER ANNEX C: SOIL ANALYSIS		EACH SUSPECT LOAD	1/SAMPLE	WITHIN 1 CALENDAR MONTH OF SAMPLE BEING TAKEN	C1(b) D1(c) D3(c) ANNEX B ANNEX E
	WASTE CONTAMINATED ABOVE LEVEL FOR THAT GROUP	FULL ANALYSIS	AS PER ANNEX C: FULL ANALYSIS		EACH SUSPECT LOAD	1/SAMPLE	WITHIN 1 CALENDAR MONTH OF SAMPLE BEING TAKEN	C1(b) D1(c) D3(c) ANNEX A ANNEX B ANNEX C
	SPECIAL WASTES AND WASTES REQUIRING ANALYSIS UNDER ANNEX A	FULL ANALYSIS OR WASTE PRODUCER'S ANALYSIS			EACH LOAD	1/SAMPLE		
SURFACE WATERS	MONITORING	DISCRETE	CONDUCTIVITY	us/cm	DAILY/MONITORING POINT	MONTHLY	WITHIN 2 WEEKS FOLLOWING END OF MONTH	D1(e) D3(e) 14 ANNEX D
	ANALYSIS	RESULTS & SUMMARY INTERPRETATION	AS PER ANNEX D		QUARTERLY/MONITORING POINT	QUARTERLY	WITHIN 1 CALENDAR MONTH OF SAMPLES BEING TAKEN	
	MONITORING	DISCRETE	CONDUCTIVITY	us/cm	QUARTERLY/MONITORING POINT	QUARTERLY	WITHIN 1 WEEK OF MEASUREMENT	D1(f) D3(f) 15 ANNEX D
GROUNDWATER	ANALYSIS	RESULTS & SUMMARY INTERPRETATION	AS PER ANNEX D		QUARTERLY/MONITORING POINT	QUARTERLY	WITHIN 1 CALENDAR MONTH OF SAMPLES BEING TAKEN	

SUBJECT	RECORD	SPECIAL WASTE REGULATIONS (1980)			FREQUENCY	SUBMISSION TO WRA		REF COMOR
		DETAILS	PARAMETERS	UNITS		FREQUENCY	DEADLINE	
SPECIAL WASTES	DAILY RECORDS	WASTE TYPE	ANNEX A	VOLUME/KILOS	EACH LOAD DELIVERED EACH STORAGE CONTAINER	MONTHLY	WITHIN TWO WEEKS FOLLOWING END OF MONTH	C4 D1(c)(1)
		QUANTITY	VOLUME/WEIGHT					
		CONDITION	DESCRIPTION					
		CONTAINER TYPE	CROSS-REFERENCE					
		CONTAINER CONDITION	TO COMBIGNMENT NOTE NUMBER					
		STORAGE LOCATION						

ANNEX F

NORTH WEST WASTE DISPOSAL AUTHORITIES - REGIONAL GROUPING CODE OF PRACTICE FOR THE DISPOSAL OF DRUMMED WASTES TO LANDFILL

1. INTRODUCTION

- 1.1 This Code of Practice is intended for the guidance of producers, carriers and disposers of drummed waste materials. The variety of materials which are disposed of in drums, and the range of physical form of the wastes, renders it impractical to try to cover every eventuality and permutation. In specific instances where doubt exists, the advice of the Waste Regulation Authority should be sought.

In particular, where a landfill site only accepts an occasional drum of waste, which in the opinion of the WRA is essentially innocuous, the WRA may, at its discretion, determine that the full requirements of the Code are inappropriate, and in such instances may agree that the procedures need not be followed into.

- 1.2 The Code is primarily intended to apply to waste contained in 200 litres (40-45 gallons) drums, of either side or end bung, or removable end variety. Additionally, in appropriate instances, the WRA may apply the Code to substantial arisings of larger or smaller containers of either metal or plastic construction.

- 1.3 The aim of the Code of Practice is to minimise the two major potential problems associated with the acceptance of drummed waste in quantity. These problems are:-

- (a) The need to ensure that the contents of each drum are in accordance with the description and that the material can be safely and satisfactorily deposited in the landfill in accordance with the conditions of the site licence or resolution.
- (b) Where a landfill site accepts a significant proportion of drummed wastes, to ensure that the deposit of drummed materials does not adversely affect the long-term settlement of the site.

The first of these needs the provision of an inspection procedure for the drums on reception, whilst the second requires the operational methods of deposit to be related to the physical and chemical nature of the wastes.

- 1.4 The drum reception procedures outlined in paragraphs 2.1 to 2.5 are to be applied at all landfill sites except where the circumstances covered in paragraph 1.8 apply.
- 1.5 The use of drums for the containment and landfilling of liquid wastes is not considered to be good practice and waste producers should, wherever possible, be encouraged to adopt alternative methods. One such alternative is the bulking of similar or compatible liquids by transfer of contents of the drums into a tank vehicle for transport to the disposal site; this alternative should be considered for accumulation of drums in excess of ten.
- 1.6 The practice of landfilling uncrushed empty drums is also undesirable. Whilst it is recognised that the nature of the former contents of the drums may in some instances render disposal necessary, waste producers should be encouraged to consider whether a light process modification would enable the drums to be re-used, recycled or recovered as scrap metal.

Annex F continued....

- 1.7 This Code relates essentially to the disposal of wastes in sound drums. Where, due to neglect by the producer, or for other reason, the drums are seriously corroded or otherwise unsound, other considerations are involved. The condition of the drums will increase the potential hazard of inspecting the contents and may also render the handling and disposal on site more difficult and hazardous. Additionally, the presence of leaking drums may necessitate transport in skip vehicles, rendering on-site inspection more difficult. Where such a situation occurs, approval of the WRA must be given for any departure from the normal requirements of the Code.
- 1.8 The Code recognises that there may be situations in which it is appropriate to permit changes to these procedures to allow off-site inspection to be undertaken; some examples are given below:-
- (a) Where the site operator also operates a suitably licensed waste transfer station or similar facility and only receives drummed wastes onto the landfill which have been checked via that facility.
 - (b) Where the operator is undertaking a drum clearance operation at a producer's site and is able to undertake the drum inspection at the site or origin.
 - (c) Where a waste producer is operating an in-house site and can again undertake the drum checking away from the deposit site.

The common factor in these examples is the direct control which can be exerted by the disposal site operator over the drum inspection procedures.

2. DRUMMED RECEPTION PROCEDURES


- 2.1 The contents of each drum shall be tested, before release for on-site disposal, to match the contents with the description given and ensure that the contents are capable of safe disposal within the terms of the licence and to confirm the technique of disposal.
- 2.2 The inspection procedures of paragraph 2.1 will normally be undertaken at the disposal site. Where this is the case, the operator shall ensure that technically competent personnel undertake the inspection and that they are provided with adequate safety and testing equipment to enable them to carry out the inspection in a safe and satisfactory manner.
- 2.3 In all instances where the inspection procedures are likely to lead to delay and necessitate the temporary storage of either drums awaiting inspection or drums which have been rejected as unsuitable for disposal, a drum reception and storage area shall be provided. The reception area should be sited so as not to impede other site operations.
- 2.4 Details of the design and construction of the reception and storage area shall be provided as part of the Working Plan for the site and may additionally be conditioned in the site licence. The storage area shall be constructed with an impermeable base, and be bunded to contain spillages and/or contaminated rainwater for approved disposal. Provision may also be required for compartmenting to cater for temporary storage of incompatible materials. Where overnight storage is required, the WRA may require additional security fencing of the reception area to supplement the existing peripheral site fencing.

Annex F continued....

- 2.5 To enable the reception and inspection procedures of paragraph 2.1 to 2.3 to be organised in an efficient manner, the operator shall maintain a booking-in system for drummed wastes, in which a waste producer or carrier gives advance notification to the site operator, of their intention to bring a load to the site and also provide a description of the intended waste.
- 2.6 As noted in paragraph 1.4 where there may be certain circumstances in which the site operator wishes to arrange for the drum inspection to be carried out at some point remote from the deposit site. This shall only be with the approval of the WRA, who will ensure that the standard of inspection of the contents of the drum is at least as good as that which could be achieved by the procedures given in paragraphs 2.1 to 2.3. Each drum from the remote inspection point shall be properly marked and accompanied by documentary evidence of inspection.

ANNEX G : TESTING OF LIQUIDS IN BUNDS

1. Any water or other liquid which collects in any of the bunds shall be subjected to the following tests prior to discharge:
 - 1.1 A 100ml representative sample of the liquid shall be transferred to a clear glass measuring cylinder and shall be allowed to stand for a minimum of 5 minutes. The following information shall then be recorded:
 - (a) date;
 - (b) location and time of sample;
 - (c) name of person taking sample;
 - (d) name of person carrying out test;
 - (e) total height of liquid in measuring cylinder;
 - (f) height of aqueous layer;
 - (g) height of organic layer;
 - (h) presence and nature of odour.
2. Liquids for which the above test either:
 - (i) show the presence of an organic layer; or
 - (ii) smell of solvent,shall not be discharged to drain, but shall be removed to a suitably licensed site for disposal.



MODIFIED TO USE
REF RD/LIC/255/82 TO
INCLUDE DIFFICULT AND
SPECIFIC WINSTES
AT TRADERS STATION
KENYON LANE, RAMSBOTTOM.

IRWELL STREET
METAL CO. LTD.

IRWELL STREET
METAL CO. LTD.

KENYON STREET

WORKS.

WORKS.

WORKS.

HARRISON ST.

STEAD ST.

PEEL BROW

LOCATION PLAN 1-1250

NOTES:

1. Contravention of the licence conditions may render the holder subject to prosecution and on summary conviction liable to a fine.
2. This licence may only be transferred by the holder in accordance with the provisions of Section 8 of the Act.
3. The holder's attention is drawn to the conditions of the licence which require that a copy of this site licence should be displayed in a prominent position at the site control office.
4. This licence refers only to the provisions of Part 1 of the Control of Pollution Act 1974, and it does not include any consent or approval under any other enactment by law, order or regulation nor does it remove the need for the holder to comply with the requirements of the Health and Safety at Work, etc Act, 1974, the Radio Active Substances Act, 1960, or any other relevant planning, water protection or environmental health legislation.
5. 'Controlled Waste' shall have meaning assigned to it by Section 30 of the Control of Pollution Act, 1974.
6. Where:-
 - a) an application for a disposal licence of a modification of a disposal licence is rejected; or
 - b) a disposal licence which specifies conditions is issued; or
 - c) the conditions specified in a disposal licence are modified; or
 - d) a disposal licence is revoked

the applicant/holder/last holder (as the case may be) may appeal to the Secretary of State in accordance with Section 10 of the Control of Pollution Act, 1974. Appeals must be notified within six months of the date of this notice to the Secretary, Department of the Environment, Waste Disposal Division, Romney House, 43 Marsham Street, London, SW1 3PY. The Secretary of State has power to allow a longer period for the giving of the notice of an appeal, but he will not normally be prepared to exercise this power unless there are special circumstances which excuse the delay in giving notice of an appeal.

7. In the event of an accident causing death or serious bodily injury to any person as a result of operations at the site, the licensee should immediately inform HM Principal Inspector of Factories, Public Service Group, Health and Safety Executive, Quay House, Quay Street, Manchester, M3 3JB.

PO Box 33
Civic Centre
Oldham OL1 1UL

Solicitor
David Shipp MA (Oxon)

Greater Manchester
**WASTE
DISPOSAL**
Authority

The Secretary,
Irwell Street Metal Co Ltd.,
Kenyon Street Works,
Ramsbottom,
Bury.

Your ref:
Our ref: CET/IT/WDA 13/2
Ask for: Mr Thorp
Doc ref: 30,25 9(g)/SM
Date: 16th March 1992

Direct Line 061 678 4711
Fax 061 678 4700

Dear Sir,

CONTROL OF POLLUTION ACT 1974
MODIFICATION TO WASTE DISPOSAL SITE
LICENCE NO. RD/LIC/255/82

I have pleasure in enclosing two copies of a Modification
(No. RD/LIC 255/82/M3) to the Licence which was issued on 5th December 1984.

I would draw your attention to the notes which are attached to the
Modification Notice. It is most important that you confirm receipt of the
Modification in writing to the Chief Officer of the Greater Manchester Waste
Regulation and Disposal Authority, Blackfriars House, Parsonage, Manchester,
M3 2JA.

Yours faithfully,

D. Shipp

Solicitor to the Authority